

30KW Yanmar Compact Diesel Generator

Yanmar Engine | 60 Hz | 1800 RPM



Genset Specifications

| | |
|---------------------------------------|--|
| Power | 30 kW 35 kVA |
| Frequency | 60 Hz |
| Speed | 1800 RPM |
| Voltage | Any voltage can be customized |
| Phase | Single phase and Three phase options available |
| Overall Dimensions (L x W x H) | 59.06 x 29.53 x 39.37 (in.) |
| Net Weight (lbs.) | 1100 |

Engine Data

| | |
|----------------------------|---------------------|
| Model | Yanmar 4TNV98-ZGGE |
| Cylinders | 4 cylinder |
| Engine Speed | 1800 RPM |
| Combustion Type | Direct Injection |
| Governor Type | Electronic |
| Aspiration | Naturally Aspirated |
| Displacement (L) | 3.32 L |
| Bore x Stroke (in.) | 3.9 x 4.3 in. |
| Electrical System | 12V-40A |
| Cooling Method | Water Pump |

Alternator Data

| | |
|-----------------------------|--------------------------------------|
| Model | Stamford SIL2-H1 |
| Excitation Mode | Self-exciting |
| Voltage Control Mode | AVR automatically regulates pressure |
| Type | Synchronous, brushless |
| Insulation Class | H |
| Protection Level | IP23 |



| | |
|--|--------------------|
| NET INTERMITTENT POWER Potencia Neta Intermitente | 54.7 hp 40.8 kW |
| RATED SPEED Velocidad de Regimen | 1800 RPM |

4TNV98-ZGGE


| SPECIFICATION Especificacion | ZGGE |
|-------------------------------------|---------------------------------|
| CYLINDERS Cilindros | 4 |
| BORE X STROKE Diámetro x Carrera | 3.9 X 4.3 (in) 98 X 110 (mm) |
| DISPLACEMENT Cilindrada | 202.5 (ci) 3319 (cc) |

| Dimensions & Performance Data & Quick Specs | Length / Longitud | 30.04 in (763 mm) |
|---|---------------------------|-------------------|
| | Width / Ancho | 21.65 in (550 mm) |
| | Height / Altura | 29.21 in (742 mm) |
| | Dry Weight / Peso en seco | 540 lbs / 245 kg |

| COMBUSTION TYPE Tipo de Combustion |
|---------------------------------------|
| Direct Injection Inyeccion Directa |

| ASPIRATION Aspiracion |
|---|
| Naturally Aspirated Aspiracion Natural |

| GOVERNOR TYPE Tipo de Gobernador |
|-------------------------------------|
| Electric Electrico |



Reliable & Durable

The TNV engines now proudly take up the running as Yanmar's premium small industrial diesel. They offer even more enhanced durability due to better block cooling, a stiffer crank and pistons, finer tolerance in the journal and more. CAE analysis has brought lower vibrations and higher strength to the mounting structure for even better reliability in heavy-duty jobs.



Clean Emissions

Building off the proven TNE design, Yanmar has achieved superior exhaust emissions by improving the combustion chamber and fuel injection equipment design. Engines are compliant with Interim Tier 4 and EU stage III A exhaust emissions regulations.



Fuel Delivery and Economy

A newly designed, Distributor-Type MP4 Fuel Injection Pump is utilized to assure more precise fuel delivery and control. The result is reduced emissions, improved performance over a wide range of applications and increased fuel economy which assures that Yanmar's reputation for superior starting characteristics continues.

Lubrication System

10.5L Capacity Deep Oil Pan

Electrical System

12V, 40 Amp Alternator

Fuel System

Distributor-Type MP4 Fuel Injection Pump

Cooling System

Water Pump, Belt Driven

Power Take Off

FWH-SAE #3 t=125
FW-SAE 11.5" CMP

STAMFORD®

S1L2-H1 Winding 06 / 706

S1L2-H1 - Technical Data Sheet

Standards

STAMFORD industrial alternators meet the requirements of IEC EN 60034 and the relevant section of other international standards such as BS5000, VDE 0530, NEMA MG1-32, IEC34, CSA C22.2-100 and AS1359. Other standards and certifications can be considered on request.

Quality Assurance

Alternators are manufactured using production procedures having a quality assurance level to BS EN ISO 9001.



Excitation and Voltage Regulators

| | |
|----------------------------------|----------------------------|
| Excitation System | |
| AVR Type | AVR Power |
| VITA01 | Self-Excited / Aux winding |
| Voltage Regulation | ± 0.5% |
| No Load Excitation Voltage (V) | 13 V |
| Full Load Excitation Voltage (V) | 53 V |

STAMFORD®

S1L2-H1 Winding 06 / 706

| Electrical Data | | |
|---|--|-------|
| Insulation System | Class H | |
| Stator Winding | Double Layer Concentric | |
| Winding Pitch | Two Thirds | |
| Winding Leads | 4 | |
| Winding Number | 06 / 706 | |
| Number of Poles | 4 | |
| IP Rating | IP23 | |
| RFI Suppression | EN 61000-6-2 & EN 61000-6-4, refer to factory for others | |
| Waveform Distortion | NO LOAD < 2% NON-DISTORTING BALANCED LINEAR LOAD < 5.0% | |
| Short Circuit Ratio | 1/Xd | |
| Steady State X/R Ratio | 3.9 | |
| 60 Hz | | |
| Telephone Interference | TIF<50 | |
| Voltage Series | 240 | 240 |
| Power Factor | 0.8 | 1.0 |
| kVA Base Rating (Class H) | 29 | 31.3 |
| Saturated Values in Per Unit at Base Ratings and Voltages | | |
| Xd Dir. Axis Synchronous | 1.027 | 1.108 |
| X'd Dir. Axis Transient | 0.132 | 0.142 |
| X" d Dir. Axis Subtransient | 0.118 | 0.127 |
| Xq Quad. Axis Reactance | 1.086 | 1.172 |
| X" q Quad. Axis Subtransient | 0.137 | 0.148 |
| XL Stator Leakage Reactance | 0.075 | 0.081 |
| X2 Negative Sequence Reactance | 0.190 | 0.205 |
| X0 Zero Sequence Reactance | 0.005 | 0.005 |
| Unsaturated Values in Per Unit at Base Ratings and Voltages | | |
| Xd Dir. Axis Synchronous | 1.438 | 1.552 |
| X'd Dir. Axis Transient | 0.152 | 0.164 |
| X" d Dir. Axis Subtransient | 0.138 | 0.149 |
| Xq Quad. Axis Reactance | 1.119 | 1.207 |
| X" q Quad. Axis Subtransient | 0.164 | 0.177 |
| XL Stator Leakage Reactance | 0.085 | 0.091 |
| X2 Negative Sequence Reactance | 0.228 | 0.246 |
| X0 Zero Sequence Reactance | 0.006 | 0.006 |
| Time Constants (Seconds) | | |
| T'd TRANSIENT TIME CONST. | 0.028 | |
| T" d SUB-TRANSTIME CONST. | 0.001 | |
| T'do O.C. FIELD TIME CONST. | 0.122 | |
| Ta ARMATURE TIME CONST. | 0.011 | |

STAMFORD®

S1L2-H1 Winding 06 / 706

| Resistances in Ohms (Ω) at 22°C | |
|--|--|
| Stator Winding Resistance (Ra) | 0.079 Ω per phase series connected |
| Rotor Winding Resistance (Rf) | 0.891 Ω |
| Exciter Stator Winding Resistance | 16.3 Ω |
| Exciter Rotor Winding Resistance | 0.100 Ω per phase |
| Positive Sequence Resistance (R1) | 0.099 Ω |
| Negative Sequence Resistance (R2) | 0.114 Ω |
| Zero Sequence Resistance (R0) | 0.099 Ω |
| Aux Winding Resistance (with winding 706 only) | 2.388 Ω |
| Mechanical data | |
| Cooling Air | 0.215 m ³ /sec (60Hz) |
| Shaft and Keys | All alternator rotors are dynamically balanced to better than BS6861: Part 1 Grade 2.5 for minimum vibration in operation. |
| Bearing | Single Bearing |
| Weight Complete Alternator | 160.2 kg |
| Weight Wound Stator | 63.39 kg |
| Weight Wound Rotor | 61.14 kg |
| Moment of Inertia | 0.2682 kgm ² |
| Shipping weight in a Crate | 207 kg |
| Packing Crate Size | 1050X570X960 mm |
| Maximum Over Speed | 2250 RPM for two minutes |
| Bearing Drive End | N/A |
| Bearing Non-Drive End | Ball Bearing, 6306-2RS1 |

STAMFORD[®]

S1L2-H1 Winding 06 / 706

RATINGS AT 0.8/1.0 POWER FACTOR

| Class - Temp Rise | Standby - 163/27°C | Standby - 150/40°C | Cont. H - 125/40°C | Cont. F - 105/40°C |
|------------------------|--------------------|--------------------|--------------------|--------------------|
| 60 Series (V) | 240 240 | 240 240 | 240 240 | 240 240 |
| Hz Power Factor | 0.8 1.0 | 0.8 1.0 | 0.8 1.0 | 0.8 1.0 |
| kVA | 31.9 34.4 | 30.7 33.2 | 29.0 31.3 | 26.3 28.3 |
| kW | 25.5 34.4 | 24.6 33.2 | 23.2 31.3 | 21.0 28.3 |
| Efficiency (%) | 79.5 83.7 | 80.0 84.1 | 80.7 84.8 | 81.6 85.5 |
| kW Input | 32.1 41.1 | 30.7 39.5 | 28.8 36.9 | 25.8 33.1 |

De-Rates

All values tabulated above are subject to the following reductions:

- 3% for every 500 meters by which the operating altitude exceeds 1000 meters above mean sea level
- 3% for every 5°C by which the operational ambient temperature exceeds 40°C
- For any other operating conditions impacting the cooling circuit please refer to applications

Note: Requirement for operating in an ambient exceeding 60°C and altitude exceeding 4000 meters must be referred to applications.

Dimensional and Torsional Drawing

For dimensional and torsional information please refer to the alternator General Arrangement and rotor drawings available on our website (<http://stamford-avk.com/>)

Note: Continuous development of our products means that the information contained in our data sheets can change without notice, and specifications should always be confirmed with Cummins Generator Technologies prior to purchase.

DSE6110/20 MKIII

AUTO START & AUTO MAINS (UTILITY) FAILURE CONTROL MODULES



DSE6110 MKIII



DSE6120 MKIII

KEY FEATURES

- 4-line back-lit LCD text display
- Multiple display languages
- Five-key menu navigation
- LCD alarm indication
- Customisable power-up text and screen images.
- DSENet® expansion compatibility
- Data logging facility
- Internal PLC editor
- Protections disable feature
- Fully configurable via PC using USB communications
- Front panel configuration with PIN protection
- Power save mode
- 3-phase generator sensing and protection
- 3-phase mains (utility) sensing and protection (DSE6120 MKIII only)
- Automatic load transfer control (DSE6120 MKIII only)
- Generator current and power monitoring (kW, kvar, kVA, pf)
- Mains (utility) current and power monitoring (kW, kvar, kVA, pf) (DSE6120 MKIII only)
- kW overload alarm
- Over current protection
- Breaker control via fascia buttons
- Fuel and start outputs configurable when using CAN
- 6 configurable DC outputs
- 4 configurable analogue/digital inputs
- Support for 0 V to 10 V & 4 mA to 20 mA sensors
- 8 configurable digital inputs
- CAN, MPU and alternator frequency speed sensing in one variant
- Real time clock
- Manual and automatic fuel pump control
- Engine pre-heat and post-heat functions
- Engine run-time scheduler
- Engine idle control for starting & stopping
- Fuel level alarms
- 3 configurable maintenance alarms
- Compatible with a wide range of CAN engines, including Tier 4 engine support
- Uses DSE Configuration Suite PC Software for simplified configuration
- Licence-free PC software
- IP65 rating (with optional gasket) offers increased resistance to water ingress
- Configurable CAN read & transmitted information.
- 1 alternative configuration.

KEY BENEFITS

- Automatically transfers between mains (utility) and generator (DSE6120 MKIII only) for convenience.
- Hours counter provides accurate information for monitoring and maintenance periods
- User-friendly set-up and button layout for ease of use
- Multiple parameters are monitored & displayed simultaneously for full visibility
- The module can be configured to suit a wide range of applications for user flexibility
- PLC editor allows user configurable functions to meet user specific application requirements.

SPECIFICATIONS

DC SUPPLY

CONTINUOUS VOLTAGE RATING
8 V to 35 V Continuous
5 V for up to 1 minute

CRANKING DROPOUTS

Able to survive 0 V for 100 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries. LEDs and backlight will not be maintained during cranking.

MAXIMUM OPERATING CURRENT

260 mA at 12 V, 150 mA at 24 V

MAXIMUM STANDBY CURRENT

145 mA at 12 V, 85 mA at 24 V

CHARGE FAIL/EXCITATION RANGE

0 V to 35 V

GENERATOR & MAINS (UTILITY)

VOLTAGE RANGE
15 V to 415 V AC (Ph to N)
26 V to 719 V AC (Ph to Ph)

FREQUENCY RANGE

3.5 Hz to 75 Hz

MAGNETIC PICKUP

VOLTAGE RANGE
+/- 0.5 V to 70 V

FREQUENCY RANGE

10,000 Hz (max)

INPUTS

DIGITAL INPUTS A TO H
Negative switching

ANALOGUE INPUTS A & D

Configurable as:
Negative switching digital input
0 V to 10 V sensor
4 mA to 20 mA sensor
Resistive sensor

ANALOGUE INPUTS B & C

Configurable as:
Negative switching digital input
Resistive sensor

OUTPUTS

OUTPUT A & B (FUEL & START)
10 A DC at supply voltage

AUXILIARY OUTPUTS C, D, E, F, G & H
2 A DC at supply voltage

DIMENSIONS

OVERALL
216 mm x 158 mm x 43 mm
8.5" x 6.2" x 1.5"

PANEL CUT-OUT

184 mm x 137 mm
7.2" x 5.3"

MAXIMUM PANEL THICKNESS

8 mm
0.3"

STORAGE TEMPERATURE RANGE

-40°C to +85°C
-40 °F to +185 °F

OPERATING TEMPERATURE RANGE

NON-HEATED DISPLAY VARIANT
-30°C to +70°C
-22 °F to +158 °F

HEATED DISPLAY VARIANT

-40 °C to +70 °C
-40 °F to +158 °F

OPTIONAL PARTS

| PART | PART NUMBER |
|-------------|-------------|
| IP65 Gasket | 020-521 |

RELATED MATERIALS

| TITLE | PART NO. |
|---|----------|
| DSE6110 MKIII & DSE6120 MKIII Installation Instructions | 053-240 |
| DSE6110 MKIII & DSE6120 MKIII Operator Manual | 057-289 |
| DSE6110 MKIII & DSE6120 MKIII Configuration Suite PC Manual | 057-290 |

DEEP SEA ELECTRONICS

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH
TELEPHONE +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303
EMAIL sales@deepseapl.com **WEBSITE** www.deepseapl.com

DEEP SEA ELECTRONICS INC USA

3230 Williams Avenue, Rockford, IL 61101-2668 USA
TELEPHONE +1 (815) 316 8706 **FACSIMILE** +1 (815) 316 8708
EMAIL sales@deepseausa.com **WEBSITE** www.deepseausa.com

DSE6110/20 MKIII

AUTO START & AUTO MAINS (UTILITY) FAILURE CONTROL MODULES

The DSE6110 MKIII is an Auto Start Control Module and the DSE6120 MKIII is an Auto Mains (Utility) Failure Control Module suitable for a wide variety of single, diesel or gas, gen-set applications.

Monitoring an extensive number of engine parameters, the modules will display warnings, shutdown and engine status information on the back-lit LCD screen, illuminated LEDs and remote PC.

The DSE6120 MKIII will also monitor the mains (utility) supply. The modules include USB connection and dedicated DSENet® terminals for system expansion.

Both modules are compatible with electronic (CAN) and non-electronic (magnetic pick-up/alternator sensing) engines and offer an extensive number of flexible inputs, outputs and extensive engine protections so the system can be easily adapted to meet the most demanding industry requirements.

The extensive list of features includes enhanced event and performance monitoring, remote communications & PLC functionality.

The modules can be easily configured using the DSE Configuration Suite PC software. Selected front panel editing is also available.

ENVIRONMENTAL TESTING STANDARDS

ELECTRO-MAGNETIC COMPATIBILITY

BS EN 61000-6-2
EMC Generic Immunity Standard for the Industrial Environment
BS EN 61000-6-4
EMC Generic Emission Standard for the Industrial Environment

ELECTRICAL SAFETY

BS EN 60950
Safety of Information Technology Equipment, including Electrical Business Equipment

TEMPERATURE

BS EN 60068-2-1
Ab/Ae Cold Test -30 °C
BS EN 60068-2-2
Bb/Be Dry Heat +70 °C

VIBRATION

BS EN 60068-2-6
Ten sweeps in each of three major axes
5 Hz to 8 Hz at +/-7.5 mm,
8 Hz to 500 Hz at 2 gn

HUMIDITY

BS EN 60068-2-30
Db Damp Heat Cyclic 20/55 °C
at 95% RH 48 Hours
BS EN 60068-2-78
Cab Damp Heat Static 40 °C
at 93% RH 48 Hours

SHOCK

BS EN 60068-2-27
Three shocks in each of three major axes
15 gn in 11 ms

DEGREES OF PROTECTION PROVIDED BY ENCLOSURES

BS EN 60529
IP65 - Front of module when installed into the control panel with the optional sealing gasket.

COMPREHENSIVE FEATURE LIST TO SUIT A WIDE VARIETY OF GEN-SET APPLICATIONS

